Cordless
Driver DrillCordless Impact
Driver DrillCordless
Impact DriverCordless
Impact DriverCordless
Impact Wrench18V DS 18DF18V DV 18DF18V WH 18DF18V WR 18DFImpact Wrench
Impact WrenchImpact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact Wrench
Impact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact Wrench
Impact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact WrenchImpact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact WrenchImpact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact WrenchImpact Wrench
Impact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact WrenchImpact Wrench
Impact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact WrenchImpact Wrench
Impact Wrench
Impact Wrench
Impact Wrench
Impact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact Wrench
Impact WrenchImpact Wrench
Impact

Specifications

| Model | | DS 18DF | DV 18DF | WH 18DF | WR 18DF |
|------------------------|--------------------|---|---|---|---|
| Battery Voltage | | 18V | | | |
| Drill Chuck | | 1.5 - 13mm Keyless | 1.5 - 13mm Keyless | - | - |
| Capacity | Brick | - | 13mm | - | - |
| | Mild Steel | 13mm | 13mm | - | - |
| | Soft Wood | 38mm | 38mm | - | - |
| | Wood Screw (D x L) | 6.8 x 50mm | 8 x 75mm | - | - |
| | Machine Screw | 6mm | 6mm | 4 - 8mm | - |
| | Bolt | - | - | M6 - M14 | M10 - M16 |
| | High-Tension Bolt | - | - | M6 - M12 | M8 - M14 |
| Square Drive | | - | - | - | 12.7mm |
| Max Torque | | Hard: 53Nm Soft: 20Nm | Hard: 55Nm Soft: 23Nm | - | - |
| Max Tightening Torque | | - | - | 150Nm*1 | 220Nm*2 |
| No Load Speed | | High: 0 - 1,250/min Low: 0 - 450/min | High: 0 - 1,400/min Low: 0 - 350/min | 0 - 2,400/min | 0 - 2,400/min |
| Impact Rate | | - | High: 0 - 19,600/min Low: 0 - 4,900/min | 0 - 3,200/min | 0 - 3,200/min |
| Overall Length | | 213mm | 218mm | 166mm | 177mm |
| Weight* ³ | | 1.7 - 2.3kg | 1.7 -2.3kg | 1.4 - 2.0kg | 1.4 - 2.0kg |
| Standard Accessories*4 | | 2 Batteries (BSL1820M), Charger (UC18YKSL), Driver Bit, Battery Cover, Carrying Case | 2 Batteries (BSL1820M), Charger (UC18YKSL), Driver Bit, Battery Cover, Carrying Case | 2 Batteries (BSL1820M), Charger (UC18YKSL), Battery Cover, Carrying Case | 2 Batteries (BSL1820M), Charger (UC18YKSL), Battery Cover, Carrying Case |


*1. When tightening an M14 high tension bolt (Grade 12.9) for three seconds with a socket adapter and a hexagonal socket (40mm in overall length) attached.

*2. When tightening an M20 (F10T) bolt for ten seconds with a hexagonal socket (40mm in overall length) attached.

*3. Weight according to EPTA-Procedure 01/2014. The weight differs depending on the attached battery. The heaviest weight is measured with the BSL36B18 battery (sold separately).

*4. Included accessories vary by country or area.

Distributed by:



Koki Holdings Co., Ltd.

Hikoki UNLEASH the NEXT

Powerful and Smooth

Reliable Performance with High Torque

NEW

Cordless Driver Drill 18V DS 18DF Cordless Impact Driver Drill 18V DV 18DF Cordless Impact Driver 18V WH 18DF Cordless Impact Wrench 18V WR 18DF

DS 180

⁷ WH 18



*1. The values are shown for reference purposes and may vary according to materials and conditions. *2. When tightening an M14 high tension bolt (Grade 12.9) for three seconds with a socket adapter and a hexagonal socket (40mm in overall length) attached. *3. When tightening an M20 (F10T) bolt for ten seconds with a hexagonal socket (40mm in overall length) attached.